

Linksys 1080p 3MP Indoor/Outdoor 360 Mini-Dome Camera for Business



LCAM0336OD

Key Features

- Low-light performance
- ePTZ functionality
- Motion detection
- Audio detection
- Wide dynamic range (WDR)
- Privacy mask
- User management
- Profile management
- Event management
- ONVIF-compliant v1.0 and v2.0
- Water-proof IP67-rated
- Vandal-proof IK10-rated
- Multi-streaming
- Built-in SD/SDHC card slot for uninterrupted recording
- POE IEEE 802.3af-compliant
- Video Surveillance Manager software

Protect your business and enhance your situational awareness with the all-purpose Linksys 1080p 3MP Indoor/Outdoor 360 Mini-Dome Camera for Business. Inside or outside your business, Linksys network cameras provide superior security, surveillance, and supervision.

- The ImmerVision Panomorph Lens displays 30 percent more than a standard fisheye lens, with maximum view (360° x 180°).
- Low-light performance with a Sony CMOS sensor and wide dynamic range (WDR).
- Motion detection and alarm/event notification help your business stay alert around the clock.
- The IP67 Weather Proof and IK10 Vandal Proof housing helps protect the system from both natural and criminal elements.
- Complies with Open Network Video Interface Forum (ONVIF) core specifications, versions 1.0 and 2.0.
- Free Video Surveillance Manager software with user, profile, and event management capabilities.

Linksys 1080p 3MP Indoor/Outdoor 360 Mini-Dome Camera for Business

Specifications

Imaging	
Sensor	3 Megapixel Sony CMOS
Maximum Image Resolution	2048 x 1536, 3MP
Video	
Maximum Frame Rate	20 fps @ 2048 x 1536 30 fps @ 1920 x 1080 30 fps @ 1280 x 720
Image Compression	H.264/MJPEG/MPEG4
Bitrate Control	Variable Bitrate and Constant Bitrate
Lens	
Fixed/Vari-focal	ImmerVision 360° Panomorph Lens
Focal Length	f = 0.98 ~ 1.02 mm
Focal Ratio	F2.0
Viewing Angle	Horizontal: 182° Vertical: 182°
Minimum Illumination	0.1 lux (B/W) 0.5 lux (Color)
Audio	
Compression	G.711/AMR
Audio Streaming	1-Way
Built-in Microphone	Y
Compliance Information	
FCC/IC	FCC/IC Class A
CE	CE Class A
Water-Proof	IP67-Rated
Vandal-Proof	IK10-Rated
Interface	
Ethernet	100Base-T
SD/SDHC Card Slot	Y
Power Supply	
Power over Ethernet	IEEE 802.3af
Maximum Power Consumption	< 6W
Environment	
Operating Temperature	-40°C ~ 50°C
Operating Humidity	10% to 80% Relative Humidity and Non-Condensing
Storage Temperature	-20°C to 60°C
Storage Humidity	5% to 90% Non-Condensing
Dimensions	
Unit Weight	0.40 kg